Technical Data



Profile 2530 Processor	Profile 3040 Processor
Maximum Plate Size	Maximum Plate Size
660 x 810mm (26.0 x 32.0")	762 x 1100mm (30.0 x 43.3")
Plate Thickness	Plate Thickness
0.6 to 7mm (0.023 - 0.275")	0.6 to 7mm (0.023 - 0.275")
Developer Tank Capacity	Developer Tank Capacity
61 Litres (16 US Gallons)	85 Litres (22.4 US Gallons)
Solvent Temperature Range	Solvent Temperature Range
20 to 40°C (68 to 104°F)	20 to 40°C (68 to 104°F)
Dimensions (LxWxH)	Dimensions (LxWxH)
1710 x 1670 x 1100mm (67.3 x 65.7 x 43.3")	2450 x 1970 x 1185mm (96.5 x 77.6 x 46.7")
Machine Weight	Machine Weight
580kg (1278lbs)	800kg (1764lbs)
Recommended Room Temp.	Recommended Room Temp.
18 to 25°C (65 to 77°F)	18 to 25°C (65 to 77°F)
Noise	Noise
Less than 70 dB(A)	Less than 70 dB(A)
Electrical Supply	Electrical Supply
220-240VAC 1P + Neutral + PE - 50 or 60Hz 380-480VAC 3P + Neutral + PE - 50/60Hz 3.5 kW Rating	220-240VAC 1P + Neutral + PE - 50 or 60Hz 380-480VAC 3P + Neutral + PE - 50/60Hz 4 kW Rating
Please specify power requirements with your order	Please specify power requirements with your order



