



**USED ART.-NO. P 1236**

**Flexo Plate Processor *BASF nyloflex Combi F III***



In-line platewasher in a self-contained design with integrated pre-dryer. Most modern technology.

The plates are processed in a very short time. They are then available already hand dry.

The processor is designed to be used with alternative solvents e.g. Nylosolv, Solvit, Optisol, Flexosol e.c.

<b>BASF plate processor COMBI F III + EDLF Format 900 x 1200 mm</b>	
incl. Punch and pin bars	

**Technical data for the BASF nyloflex Combi F III processor**




Year of manufacture	2001
Max. plate size	90 x 120 cm
Length	330 cm
Width	170 cm
Hight	120 cm
Weight net	500 kg
Weight gross	1400 kg
Power requirements	5 kW



**Exposur/Dryer/ Light-Finisher - *BASF Combi F III***  
**for flexo-printing-plates**



With this all-in-one-unit you are in the position to produce a plate size of 900 x 1200 mm.

-  Exposure
-  Dryer
-  Light-Finisher

EXPOSURE	Tube flat-exposure 21 UV-A, 80W/10R Yellow tube for easy inspection Vacuum role in a handy dispenser Computer controlled timer for back exposure Computer controlled timer for main exposer
DRYER	4 Dryer drawers
LIGHT-FINISHER + Post-Exposure	18 UV-C TUV 36, 36 W – 19 UV-A 60W-10R

Year of manufacture	2001
Max. plate format	90 x 120 cm
Length	165 cm
Width	130 cm
Hight	130 cm
Weight	250 kg
Power	8,5 KW
	400V 3 N/50 Hz